



# Material Safety Data Sheet

The Dow Chemical Company

**Product Name:** GREAT STUFF(TM) Pro Gun Cleaner

**Issue Date:** 11/28/2007  
**Print Date:** 29 Nov 2007

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Product and Company Identification

### Product Name

GREAT STUFF(TM) Pro Gun Cleaner

### COMPANY IDENTIFICATION

The Dow Chemical Company  
2030 Willard H. Dow Center  
Midland, MI 48674  
USA

Customer Information Number: 800-258-2436

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 989-636-4400  
**Local Emergency Contact:** 989-636-4400

## 2. Hazards Identification

### Emergency Overview

**Color:** Colorless

**Physical State:** Liquid

**Odor:** Mild

### Hazards of product:

**DANGER!** Flammable gas - May cause flash fire. Causes eye irritation. May cause central nervous system effects; can cause death if too much is breathed. Vapor reduces oxygen available for breathing. May cause anesthetic effects. May cause central nervous system effects; may cause respiratory tract irritation. Aspiration hazard. Can enter lungs and cause damage. Vapor explosion hazard. Vapors may travel a long distance; ignition and/or flash back may occur. Evacuate area. Keep upwind of spill. Stay out of low areas. Warn public of downwind explosion hazard. Aerosol cans exposed to fire can rupture becoming flaming projectiles. Eliminate ignition sources. Contents under pressure.

### OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

®(TM)\*Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

**Potential Health Effects**

**Eye Contact:** May cause severe eye irritation. May cause slight corneal injury. Effects may be slow to heal. Vapor may cause eye irritation experienced as mild discomfort and redness.

**Skin Contact:** Essentially nonirritating to skin. May cause drying and flaking of the skin.

**Skin Absorption:** Prolonged skin contact is unlikely to result in absorption of harmful amounts.

**Inhalation:** In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause respiratory irritation and central nervous system depression. At air concentrations <1000 ppm, propane exerts very little physiological action; at 100,000 ppm and above it may produce dizziness or other central nervous system effects. Excessive exposure may cause headache, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death.

**Ingestion:** Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

**Effects of Repeated Exposure:** Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. In animals, effects have been reported on the following organs: Blood. Kidney. Liver. Development of cataracts has been reported in laboratory animals after prolonged repeated skin exposure to acetone.

**Birth Defects/Developmental Effects:** For the component(s) tested: Acetone. Has been toxic to the fetus in lab animals at doses toxic to the mother.

**3. Composition Information**

Component	CAS #	Amount
Acetone	67-64-1	>= 60.0 - <= 100.0 %
Propane	74-98-6	>= 10.0 - <= 30.0 %

**4. First-aid measures**

**Eye Contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

**Skin Contact:** Wash skin with plenty of water.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**Notes to Physician:** Maintain adequate ventilation and oxygenation of the patient. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. The decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

**Medical Conditions Aggravated by Exposure:** Skin contact may aggravate preexisting dermatitis.

**5. Fire Fighting Measures**

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

**Unusual Fire and Explosion Hazards:** Contains flammable propellant. Aerosol cans exposed to fire can rupture and become flaming projectiles. Propellant release may result in a fireball. Container may vent and/or rupture due to fire. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

## 6. Accidental Release Measures

**Steps to be Taken if Material is Released or Spilled:** Pump with explosion-proof equipment. If available, use foam to smother or suppress. See Section 13, Disposal Considerations, for additional information.

**Personal Precautions:** Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Evacuate area. Refer to Section 7, Handling, for additional precautionary measures. Keep personnel out of low areas. Keep personnel out of confined or poorly ventilated areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Only trained and properly protected personnel must be involved in clean-up operations. Confined space entry procedures must be followed before entering the area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Vapor explosion hazard. Keep out of sewers. See Section 10 for more specific information.

**Environmental Precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

## 7. Handling and Storage

### Handling

**General Handling:** Keep away from heat, sparks and flame. Avoid contact with eyes. Wash thoroughly after handling. Do not swallow. Avoid breathing vapor. Use only with adequate ventilation. Keep container closed. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Ignition sources can include and are not limited to pilot lights, flames, smoking, sparks, heaters, electrical equipment, and static discharges. Electrically bond and ground all containers and equipment before transfer or use of material. Never use air pressure for transferring product. Contents under pressure. Do not puncture or incinerate container. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Do not enter confined spaces unless adequately ventilated.

Keep out of reach of children. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

### Storage

Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Flammable mixtures may exist within the vapor space of containers at room temperature. See Section 10 for more specific information.

## 8. Exposure Controls / Personal Protection

### Exposure Limits

Component	List	Type	Value
Acetone	ACGIH	TWA	500 ppm
	ACGIH	STEL	750 ppm
	OSHA Table Z-1	PEL	2,400 mg/m <sup>3</sup> 1,000 ppm
Propane	OSHA Table Z-1	PEL	1,800 mg/m <sup>3</sup> 1,000 ppm
	ACGIH	TWA	1,000 ppm

A BEI notation following the exposure guideline refers to a guidance value for assessing biological monitoring results as an indicator of the uptake of a substance from all routes of exposures.

### Personal Protection

**Eye/Face Protection:** Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

**Skin Protection:** Wear clean, body-covering clothing.

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Natural rubber ("latex"). Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Respiratory Protection:** Atmospheric levels should be maintained below the exposure guideline.

**Ingestion:** Avoid ingestion of even very small amounts; do not consume or store food or tobacco in the work area; wash hands and face before smoking or eating.

### Engineering Controls

**Ventilation:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only in enclosed systems or with local exhaust ventilation. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. Lethal concentrations may exist in areas with poor ventilation.

## 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Mild
Flash Point - Closed Cup	Flammable gas.
Flammable Limits In Air	Lower: 2.1 %(V) Vendor

<b>Autoignition Temperature</b>	<b>Upper:</b> 8.5 %(V) <i>Vendor</i> (propane) 450 °C (842 °F) <i>Estimated</i>
<b>Vapor Pressure</b>	4,482 hPa <i>Vendor</i>
<b>Boiling Point (760 mmHg)</b>	No test data available.
<b>Vapor Density (air = 1)</b>	greater than air
<b>Specific Gravity (H2O = 1)</b>	0.87 <i>Vendor</i>
<b>Freezing Point</b>	No test data available
<b>Melting Point</b>	No test data available
<b>Solubility in Water (by weight)</b>	Complete
<b>pH</b>	No test data available

## 10. Stability and Reactivity

### Stability/Instability

Thermally stable at typical use temperatures.

**Conditions to Avoid:** Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

**Incompatible Materials:** Avoid contact with: Amines. Ammonia. Chlorine. Halogens. Strong acids. Strong bases. Strong oxidizers.

### Hazardous Polymerization

Will not occur.

### Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials.

## 11. Toxicological Information

### Acute Toxicity

#### Ingestion

Single dose oral LD50 has not been determined. Estimated LD50, Rat > 5,000 mg/kg

#### Skin Absorption

The dermal LD50 has not been determined. Estimated LD50, Rabbit 20,000 mg/kg

### Repeated Dose Toxicity

Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. In animals, effects have been reported on the following organs: Blood. Kidney. Liver. Development of cataracts has been reported in laboratory animals after prolonged repeated skin exposure to acetone.

### Developmental Toxicity

For the component(s) tested: Acetone. Has been toxic to the fetus in lab animals at doses toxic to the mother.

### Genetic Toxicology

For the component(s) tested: Acetone. In vitro genetic toxicity studies were predominantly negative.

## 12. Ecological Information

### CHEMICAL FATE

Data for Component: **Acetone**

#### Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is very high (Koc between 0 and 50).

**Henry's Law Constant (H):** 1.38E-5 atm\*m3/mole; 25 °C Estimated  
**Partition coefficient, n-octanol/water (log Pow):** -0.24 Measured  
**Partition coefficient, soil organic carbon/water (Koc):** 0.37 - 2.0 Estimated  
**Distribution in Environment: Mackay Level 1 Fugacity Model:**

Air	Water.	Biota	Soil	Sediment
44.3 %	55.6 %	< 0.1 %	< 0.1 %	< 0.1 %

#### Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

#### Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
2.04E-13 cm3/s	52 d	Estimated

#### OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
91 %	28 d	OECD 301B Test

**Theoretical Oxygen Demand:** 2.20 mg/mg

#### Data for Component: Propane

#### Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is very high (Koc between 0 and 50).

**Henry's Law Constant (H):** 7.07E-01 atm\*m3/mole; 25 °C Measured

**Partition coefficient, n-octanol/water (log Pow):** 2.36 Measured

**Partition coefficient, soil organic carbon/water (Koc):** 24 - 460 Estimated

**Distribution in Environment: Mackay Level 1 Fugacity Model:**

Air	Water.	Biota	Soil	Sediment
100 %	0 %	0 %	0 %	0 %

#### Persistence and Degradability

#### Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
1.27E-12 cm3/s	8.4 d	Estimated

**Theoretical Oxygen Demand:** 3.64 mg/mg

### ECOTOXICITY

#### Data for Component: Acetone

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100 mg/L in the most sensitive species tested).

#### Fish Acute & Prolonged Toxicity

LC50, rainbow trout (*Oncorhynchus mykiss*), 96 h: 5,500 - 6,100 mg/l

#### Aquatic Invertebrate Acute Toxicity

EC50, water flea *Daphnia magna*, 48 h, immobilization: 6,084 mg/l

#### Aquatic Plant Toxicity

EC50, diatom *Skeletonema costatum*, biomass growth inhibition, 5 d: 11,800 - 14,400 mg/l

#### Toxicity to Micro-organisms

IC50, OECD 209 Test; activated sludge, respiration inhibition, 3 h: > 1,000 mg/l

#### Data for Component: Propane

No relevant information found.

## 13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING

OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15 As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

## 14. Transport Information

### DOT Non-Bulk

**Proper Shipping Name:** AEROSOLS

**Hazard Class:** 2.1 **ID Number:** UN1950  
LIMITED QUANTITY

### DOT Bulk

NOT AVAILABLE IN BULK CONTAINERS

### IMDG

**Proper Shipping Name:** AEROSOLS

**Hazard Class:** 2.1 **ID Number:** UN1950

**EMS Number:** F-D,S-U

LIMITED QUANTITY

### ICAO/IATA

**Proper Shipping Name:** AEROSOLS, FLAMMABLE

**Hazard Class:** 2.1 **ID Number:** UN1950

LIMITED QUANTITY

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

## 15. Regulatory Information

### OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

<b>Immediate (Acute) Health Hazard</b>	Yes
<b>Delayed (Chronic) Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Reactive Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	Yes

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:**

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
Acetone	67-64-1	>= 60.0 - <= 100.0 %
Propane	74-98-6	>= 10.0 - <= 30.0 %

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

**US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

**CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

<b>16. Other Information</b>
------------------------------

**Recommended Uses and Restrictions**

Cleaner. Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group.

**Revision**

Identification Number: 64097 / 0000 / Issue Date 11/28/2007 / Version: 2.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

*The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with*

*all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*