



HENKEL CORPORATION
6685 KENNEDY ROAD, SUITE #1
MISSISSAUGA, ONTARIO CANADA L5T 3A5
(905) 696-2770

PRODUCT : LEPAGE SUREGRIP CARPENTERS GLUE

SECTION 01: PRODUCT INFORMATION

MANUFACTURER.....HENKEL CORPORATION
6685 KENNEDY ROAD, SUITE #1
MISSISSAUGA, ONTARIO
CANADA ; L5T 3A5
(905) 696-2770
AFTER HOURS - CANUTEC (613) 996-6666

WHMIS CLASSIFICATION.....NONE
T.D.G. CLASSIFICATION.....NOT REGULATED
PRODUCT NAME.....LEPAGE SUREGRIP CARPENTERS GLUE
CHEMICAL FAMILY.....VINYL ACETATE COPOLYMER
MATERIAL USE.....WOODWORKING ADHESIVE

SECTION 02: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	EXPOSURE LEVELS	C.A.S. #	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
Considered non-hazardous as per WHMIS regulations.		Not available			

SECTION 03: PHYSICAL DATA

PHYSICAL STATE.....Viscous liquid
APPEARANCE & ODOUR.....Light yellow liquid
ODOUR THRESHOLD (ppm).....Not available
VAPOUR PRESSURE (mm Hg).....17 mm Hg @ 20 deg C
VAPOUR DENSITY (AIR=1).....0.62
BY VOLUME
BY WEIGHT
EVAPORATION RATE.....1 (water)
BOILING POINT (deg C).....100 deg C
pH.....4.0-5.0
SPECIFIC GRAVITY.....1.08
SOLUBILITY IN WATER (% W/W).....Miscible
COEFFICIENT OF WATER/OIL.....Not available
DISTRIBUTION

SECTION 04: FIRE & EXPLOSION DATA

FLAMMABILITY.....None
IF YES, UNDER WHICH CONDITIONS?.....Not applicable
AUTO IGNITION TEMPERATURE.....Not available
EXTINGUISHING MEDIA.....Foam, "Alcohol" Foam, CO2, Dry Chemical, Water Fog.
SPECIAL PROCEDURES.....Fire fighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.
FLASH POINT (C), METHOD.....Not applicable
LOWER FLAMMABLE LIMIT (% VOL).....Not applicable
UPPER FLAMMABLE LIMIT (% VOL).....Not applicable
HAZARDOUS COMBUSTION PRODUCTS....Oxides of carbon (CO,CO2). Acetic acid

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY:
YES.....Under normal conditions
NO, WHICH CONDITIONS ?
COMPATIBILITY WITH OTHER
SUBSTANCES:
YES
NO, WHICH ONES?.....Strong oxidizing agents
REACTIVITY CONDITIONS ?.....On contact with water
HAZARDOUS PRODUCTS OF.....Oxides of carbon (CO,CO2) at high temperatures.
DECOMPOSITION

SECTION 06: TOXICOLOGICAL PROPERTIES

SKIN CONTACT.....May cause irritation, especially on prolonged contact.
SKIN ABSORPTION.....No data
EYE CONTACT.....Slightly irritating but does not cause eye tissue damage.
INHALATION.....Not expected to be a hazard due to low volatility under standard conditions. Exposure to mist or spray may cause irritation of respiratory passages.

PRODUCT : LEPAGE SUREGRIP CARPENTERS GLUE

SECTION 06: TOXICOLOGICAL PROPERTIES

INGESTION.....Low toxicity
 EFFECTS OF ACUTE EXPOSURE.....Refer to route of entry.
 EFFECTS OF CHRONIC EXPOSURE.....Product may contain small amounts of residual vinyl acetate. Vinyl acetate vapours have been shown to cause tumors in the respiratory tract of laboratory animals exposed to 600 ppm over a lifetime; 200 ppm caused irritation; 50 ppm produced no observable effect. There is no evidence of adverse effects to humans exposed to levels at or below the ACGIH TLV. May aggravate existing eye, skin, and lung conditions.

LD 50 OF MATERIAL, SPECIES &.....Not available
 ROUTE
 LC 50 OF MATERIAL, SPECIES &.....Not available
 ROUTE
 EXPOSURE LIMIT OF MATERIAL.....Not available
 IRRITANCY OF MATERIAL.....Not available
 SENSITIZING CAPABILITY OF.....None known
 MATERIAL
 CARCINOGENICITY OF MATERIAL.....No
 SYNERGISTIC MATERIALS.....Not available

SECTION 07: PREVENTATIVE MEASURES

GLOVES/ TYPE.....Chemical resistant gloves.
 RESPIRATORY/TYPE.....None required under normal use. Use a NIOSH/MSHA approved respirator whenever mist or spray is generated.
 EYE/TYPE.....Safety glasses with side-shields
 FOOTWEAR/TYPE.....Standard work shoes.
 CLOTHING/TYPE.....Standard work clothes.
 VENTILATION REQUIREMENTS.....Use adequate local exhaust ventilation.
 LEAK/SPILL.....Spills should be taken up with suitable absorbent and placed in containers. Spill area can be washed with water; collect wash water for approved disposal. Do not flush to storm sewer or waterway.
 WASTE DISPOSAL.....In accordance with municipal, provincial and federal regulations.
 HANDLING PROCEDURES AND.....Use adequate ventilation. Avoid breathing vapours. Wash thoroughly after handling.
 EQUIPMENT
 STORAGE NEEDS.....None.
 SPECIAL SHIPPING INSTRUCTIONS...Not regulated

SECTION 08: FIRST AID MEASURES

EYE CONTACT.....Immediately flush with water for a minimum of 15 minutes holding lids apart to ensure flushing of entire surface. Washing within 1 minute is essential to achieve maximum effectiveness. If irritation persists, get medical attention.
 INGESTION.....If individual is conscious, give water to dilute stomach contents. Call a physician or Poison Control Centre immediately. DO NOT attempt to give anything by mouth to a drowsy or unconscious person.
 INHALATION.....Remove to fresh air. If symptoms develop, seek medical attention.
 SKIN CONTACT.....Remove contaminated clothing. Wash affected area with water and soap. Seek medical attention if irritation occurs or persists.

SECTION 09: PREPARATION INFORMATION

PREPARED BY:.....Regulatory Affairs
 TELEPHONE NUMBER:.....(440) 937-7000
 DISCLAIMER2:.....All information, recommendations, and suggestions appearing herein concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, express or implied, is made by Henkel Consumer Adhesives as to the effects of such use, the results obtained, or the safety and toxicity of the product nor does Henkel Consumer Adhesives assume any liability arising out of use, by others, of the product referred to herein. The information herein is not to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

PREPARATION DATE.....JAN 11/2008

CANUTEC EMERGENCY (613) 996-6666