



**KLINGSPOR**  
*The Most Sanding Power for Your Money!®*

## Material Safety Data Sheet

Company: KLINGSPOR ABRASIVES, INC.  
PO Box 2367  
2555 Tate Blvd. SE  
Hickory NC 28603-2367  
tel. 828-322-3030  
fax. 828-326-0296

---

**Product name:** **ULTRAFLEX PADS**

Date of issue : January 01, 2006

DESCRIPTION: Abrasive Sanding Pad

USES: All Sanding applications on metal, wood, plastics and paintwork. Flexibility allows use in awkward places. Can be used wet or dry. After use clean under tap to remove sanding swarf and store for further use. Can give up to ten times the life of conventional sandpapers

PHYSICAL APPEARANCE: Grey foam and coated on one side with abrasive

SIZE: 140mm x 115mm x 6mm (tolerance +/- 2mm)

COMPOSITION: Polyurethane foam coat with nitrite rubber based adhesive and coated with silicon carbide or aluminum oxide abrasive

HAZARDS: Product are classified as Non- Hazardous

FIRST AID MEASURES:

Inhalation - No hazard in normal  
Skin Contact - No hazard in normal use  
Eye Contact - Wash with water to remove any particles  
Ingestion - Wash mouth and seek medical attention

SAFETY INFORMATION: The wearing of a dust mask and safety glasses is recommended when using abrasives.

HANDING AND STORAGE: Store away from direct sunlight and heat sources. Avoid any sources of ignition.

ECOLOGICAL INFORMATION: Material is inert and insoluble in water

DISPOSAL CONSIDERATIONS: Landfill

REGULATORY INFORMATION: None