

**BUTYL WHITE**Version 2.  
REVISION DATE: 04/14/2010

Print Date 04/15/2010

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : BUTYL WHITE  
Product code : 982806 323

COMPANY : Tremco Incorporated  
3735 Green Road  
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

White. Non-sag gunnable paste. No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract.  
Eyes : Slightly irritating.  
Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.  
Skin : Irritant effect may be delayed.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**SECTION 3 - PRODUCT COMPOSITION**

## BUTYL WHITE

Version 2.

Print Date 04/15/2010

REVISION DATE: 04/14/2010

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	40.0 - 70.0
Polybutene	9003-29-6	10.0 - 30.0
Stoddard solvent (Mineral Spirits)	8052-41-3	10.0 - 30.0
Butyl rubber	9060-33-7	5.0 - 10.0
Talc	14807-96-6	5.0 - 10.0
Xylene	1330-20-7	1.0 - 5.0
Ethylbenzene	100-41-4	- <1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	Not available.
Method	:	Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

### SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Do not use in confined or poorly ventilated areas. Store in sealed containers in a cool, dry, ventilated warehouse location.

**BUTYL WHITE**

Version 2.

Print Date 04/15/2010

REVISION DATE: 04/14/2010

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

**Exposure Limits**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Regulation</b>	<b>Limit</b>	<b>Form</b>
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Stoddard solvent (Mineral Spirits)	8052-41-3	ACGIH TWA: OSHA PEL:	100 ppm 2,900 mg/m3	
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

**BUTYL WHITE**

Version 2.  
REVISION DATE: 04/14/2010

Print Date 04/15/2010

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form	:	Non-sag gunnable paste
Color	:	White
Odor	:	Petroleum
pH	:	Not available.
Vapour pressure	:	Not available.
Vapor density	:	Heavier than air
Melting point/range	:	Not available.
Freezing point	:	Not available.
Boiling point/range	:	Not available.
Water solubility	:	Negligible
Specific Gravity	:	1.46
% Volatile Weight	:	15 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	:	Oxidizing agents.
Stability	:	Material is stable under normal storage, handling, and use.
Hazardous polymerization	:	Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.



**BUTYL WHITE**

Version 2.  
REVISION DATE: 04/14/2010

Print Date 04/15/2010

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

This product or its components are listed on, or exempt from the Canadian Domestic Substances List. All components are listed or exempt from the TSCA inventory.

**U.S. Federal Regulations:**

SARA 313 Components : Xylene 1330-20-7  
Ethylbenzene 100-41-4

SARA 311/312 Hazards : Acute Health Hazard

**OSHA Hazardous Components :**

Calcium Carbonate (Limestone) 1317-65-3  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Talc 14807-96-6  
Xylene 1330-20-7  
Ethylbenzene 100-41-4  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant  
hazardous based on the  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 223 g/l  
exempt solvent)

VOC Method 310 : 15 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Talc 14807-96-6  
Xylene 1330-20-7

Penn RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Polybutene 9003-29-6  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Butyl rubber 9060-33-7  
Talc 14807-96-6  
Xylene 1330-20-7



**BUTYL WHITE**

Version 2.  
REVISION DATE: 04/14/2010

Print Date 04/15/2010

NJ RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Polybutene	9003-29-6
		Stoddard solvent (Mineral Spirits)	8052-41-3
		Butyl rubber	9060-33-7
		Talc	14807-96-6
		Xylene	1330-20-7
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	2
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System